

MOTUL*fluid force*

4-Stroke

TEKMA MEGA X***15W40**

A super high performance diesel lubricant, TEKMA MEGA X* 15W-40 is specially designed for heavy machinery with naturally aspirated or turbocharged diesel engines. TEKMA MEGA X* 15W-40 features superior and highly effective anti-oxidation, anti-wear and anti-foam properties that protect engines from soot formation, piston deposits and oil filter plugging.

SPECIFICATIONS**Product**

TEKMA MEGA X*

Feature

Features superior anti-oxidation, anti-corrosion and anti-foam properties. Extends engines lifespan and keeps them clean.

SAE/DOT Standard

15W40

Specification

API CH4/SG & ACEA E5/E3

Maker's Approval

MB228.3, VOLVO VDS 2, MTU Type II, CUMMINS 20071-72, MAN M3275, RVI RLD/RD & MACK EO-M PLUS

Compatibility

All types of naturally aspirated or turbocharged diesel engines inline with EURO II or US regulations.

PRODUCT LINE-UP >>

webmaster@motul.com.sg

Content, design and layout is Copyright ©2008
HIGH-TECH LUBRICANTS AP PTE.LTD.

All Rights Reserved. Reproduction in whole or in part in any form or medium without the expressed written permission of HIGH-TECH LUBRICANTS AP PTE.LTD. is strictly prohibited.